



HIGH SPEC • HEAVY DUTY • HIGH STANDARDS

LX

Series

HEAVY DUTY
SELF-PROPELLED
VERTICAL LIFTS

- **LX31**
- **LX41**
- **LX50**

UpRight

SPECIFICATIONS	LX31	LX41	LX50
Max. working height	11.5m	14.3m	17.0m
Max. platform height	9.44m	12.34m	15.09m
Min. platform height	1.64m	1.87m	1.93m
Platform capacity	907kg	680kg	454kg
Platform size	1.78m x 3.65m	1.78m x 3.65m	1.78m x 3.65m
Platform size (with deck extension)	1.73m x 4.57m	1.73m x 4.57m	1.73m x 4.57m
Overall width	2.29m	2.29m	2.29m
Overall length - deck in	4.06m	4.06m	4.06m
Overall length - deck extended	4.62m	4.62m	4.62m
Overall height - guardrails up	2.53m	2.76m	3.00m
Height - guardrails lowered	1.64m	1.87m	2.10m
Gross weight - 2WD	4,378kg	4,985kg	5,702kg
Gross weight - 4WD	4,541kg	5,148kg	5,865kg
Inside turning radius	1.2m	1.2m	1.2m
Gradeability - 2 wheel drive	30%	30%	21%
Gradeability - 4 wheel drive	35%	35%	25%
Drive speed - lowered	0 - 5.0km/h	0 - 5.0km/h	0 - 5.0km/h
Drive speed - elevated	0 - 0.48km/h	0 - 0.48km/h	0 - 0.48km/h
Lift speed to max. height	40 seconds	45 seconds	80 seconds
Lower speed from max. height	60 seconds	65 seconds	100 seconds
Power source	Kubota D905 water cooled diesel engine	Kubota D905 water cooled diesel engine	Kubota D905 water cooled diesel engine
Tyres	10x16.5 NHS 8ply air	10x16.5 NHS 8ply air	10x16.5 NHS 8ply poly filled
Toeboards	150 mm	150 mm	150 mm

STANDARD FEATURES

Proportional joystick control
Easy access service modules
Oscillating front axle on 4WD models
Descent alarm
Tilt alarm
Weatherproof electrical enclosure
Quick-fold guardrails
Multiple disc, dual wheel parking brake

OPTIONAL EXTRAS

0.91m roll-out deck
Hydraulic levelling lacks (4)
Poly-filled tyres (on LX31 and LX41)
Warning horn on control box
Motion alarm (forward/reverse)
Exhaust scrubber
Gsoline/dual fuel engine
Removable controller
Exhaust scrubber

MANUFACTURED BY

UpRight

CE This product is available with the CE mark
confirming compliance with all relevant
European Machinery Directives.

UpRight

EUROPE

Pottery Road, Dun Laoire, Ireland.
Tel: +353 1 202 4100
Fax: +353 1 202 4102
Internet: <http://www.uprighteuro.com>