

# UpRight MXC15/MXC19 Lifts

## Self-Propelled Track Lifts



- ◆ Traverses rough terrain jobsites
- ◆ Narrow, compact lift maneuvers well in confined areas
- ◆ Turns on machine center with counter-rotating tracks
- ◆ Lightweight, easy to transport
- ◆ Driveable at full height
- ◆ Non-marking rubber track
- ◆ Fully proportional, one hand joystick controls
- ◆ All metal deck with slip-resistant surface
- ◆ Dual track drive, hydraulic motors
- ◆ Slide-out service trays
- ◆ 5-year structural warranty



# UpRight



## Self-Propelled Track Lifts

- ◆ Non-marking track
- ◆ Tilt alarm, descent alarm
- ◆ Slide-out service trays
- ◆ Lift-up rear guardrail to ease loading
- ◆ Ground view grates in deck extension
- ◆ Crane and forklift points

Technical drawings of the Genie Z-60 scissor lift showing side and front views in both retracted and extended positions.

**Side View (Left):**

- Platform width: 98.5 in. (2.50 m)
- Platform height (retracted): 19.1 ft. (5.82 m)
- Platform height (extended): 25.1 ft. (7.65 m)

**Side View (Right):**

- Platform width: 95.5 in. (2.43 m)
- Platform height (retracted): 15.1 ft. (4.60 m)
- Platform height (extended): 21.5 ft. (6.55 m)

**Front View (Left):**

- Platform width: 68.74 in. (17.4 m)

**Front View (Right):**

- Platform width: 68.74 in. (17.4 m)

**Front View (Bottom Left):**

- Platform width: 35 in. (0.89 m)
- Platform height: 82.4 in. (2.09 m)

**Front View (Bottom Right):**

- Platform width: 35 in. (0.89 m)
- Platform height: 77.5 in. (1.97 m)

Control system . . . . .	Smooth, one-hand joystick with proportional controls
Drive system . . . . .	Dual track drive, hydraulic motors
Track . . . . .	200 mm x 41 mm x 72FR rubber, non-marking
Power source . . . . .	(2) 24V 4 HP DC electric motor 4 x 6V 220 AH batteries
Battery charger . . . . .	25 amp automatic with ammeter
Parking brake . . . . .	Spring-applied hydraulic disc and manual release

- ◆ .91m (3 ft.) roll-out deck extension

Meets or exceeds applicable requirements of OSHA and ANSI A92.6 – 1990.

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate UpRight Operator's manual for detailed instructions on the proper use and maintenance of this equipment.

# UpRight

**USA (800) 926-5438, (209) 891-5200 FAX (209) 896-9012**

1775 Park Street, Selma CA 93662

**Europe (353) 1-202-4100 FAX (353) 1-202-4101**

Pottery Road, Dun Laoire, Ireland

www.upright.com e-mail: marketing@upright.com

Printed in U.S.A. Copyright UpRight, Inc. 1998. Form No. 308-980210-A