

UpRight SB60

Telescopic Boom Lifts



- ◆ Two section, 60 ft. telescopic boom
- ◆ Closer to work using 8 ft. jib with 150° arc
- ◆ 52 ft. 8 in. horizontal outreach
- ◆ 4WD, oscillating front axle
- ◆ Excellent maneuverability in rough terrain
- ◆ 45% gradeability
- ◆ Smooth, user friendly proportional controls: lifting, telescoping, rotating
- ◆ Responsive - 97 seconds to 60 ft., 4 mph ground travel speed
- ◆ 180° hydraulic platform rotation
- ◆ 360° continuous rotation
- ◆ Choice of 6 ft. or 8 ft. platforms
- ◆ Four wheel brakes

**Powerful GM Gasoline or
Perkins Diesel Engines**

UpRight

UpRight SB60

Telescopic Boom Lifts

SPECIFICATIONS	SB60 4WD Gasoline/Dual Fuel		SB60 4WD Diesel	
	U.S.	Metric	U.S.	Metric
WORKING HEIGHT	66 ft.**	20.3 m**	66 ft.**	20.3 m**
PLATFORM HEIGHT	60 ft.	18.3 m	60 ft.	18.3 m
HORIZONTAL OUTREACH	52 ft. 8 in.	16 m	52 ft. 8 in.	16 m
JIB LENGTH	8 ft.	2.4 m	8 ft.	2.4 m
JIB ARC	150°	150°	150°	150°
STD. PLATFORM SIZE - outside	39 in. x 72 in.	.99 m x 1.83 m	39 in. x 72 in.	.99 m x 1.83 m
OPT. 8 FT. (2.4 M) PLATFORM	39 in. x 96 in.	.99 m x 2.44 m	39 in. x 96 in.	.99 m x 2.44 m
PLATFORM CAPACITY - maximum	500 lbs.	227 kg	500 lbs.	227 kg
MAX. NO. OF OCCUPANTS	2	2	2	2
PLATFORM ROTATION	180° hydraulic	180° hydraulic	180° hydraulic	180° hydraulic
TURRET ROTATION	continuous	continuous	continuous	continuous
STOWED HEIGHT	8 ft. 6 in.	2.59 m	8 ft. 6 in.	2.59 m
LENGTH (operational position)	36 ft. 9.5 in.	11.21 m	36 ft. 9.5 in.	11.21 m
STOWED LENGTH (for transport)	29 ft. 9 in.	9.07 m	29 ft. 9 in.	9.07 m
WIDTH	7 ft. 11.75 in.	2.43 m	7 ft. 11.75 in.	2.43 m
INSIDE TURNING RADIUS	13 ft.	3.96 m	13 ft.	3.96 m
OUTSIDE TURNING RADIUS	22 ft. 2 in.	6.76 m	22 ft. 2 in.	6.76 m
TAILSWING - stowed	53 in.	1.35 m	53 in.	1.35 m
DRIVE SPEED - boom stowed, travel	4.0 mph	6.4 km/h	4.0 mph	6.4 km/h
DRIVE SPEED - boom elevated	.7 mph	1.2 km/h	.7 mph	1.2 km/h
GRADEABILITY - 4WD	45%	24°	45%	24°
ENGINE	GM 3.0 L	GM 3.0 L	Perkins 704-30	Perkins 704-30
AIR-FILLED TIRES	15 x19.5 14 ply	15 x19.5 14 ply	15 x19.5 14 ply	15 x19.5 14 ply
POLY-FILLED TIRES	optional	optional	optional	optional
WHEEL BASE	8 ft. 6 in.	2.59 m	8 ft. 6 in.	2.59 m
GROUND CLEARANCE	11.5 in.	.29 m	11.5 in.	.29 m
TOEBOARDS	6 in.	.15 m	6 in.	.15 m
GUARDRAIL HEIGHT	45 in.	1.14 m	45 in.	1.14 m
GROSS WEIGHT	23,600 lbs.	10,705 kg	23,700 lbs.	10,750 kg
STANDARD/OPTIONAL FEATURES				
Cycle Time to Full Height	97 seconds	97 seconds	97 seconds	97 seconds
Proportional Controls lift, swing, telescope	standard	standard	standard	standard
Dual Fuel/Propane for Gas Model	optional	optional	n/a	n/a
AC Power to the Platform	standard	standard	standard	standard
Hour Meter	standard	standard	standard	standard
Motion Alarm, Flashing Amber Beacon	optional	optional	optional	optional
Horn	optional	optional	optional	optional

*Meets or exceeds applicable requirements of OSHA and ANSI A92.5-1992. Specifications subject to change without notice.

**Working height in the U.S. is 6 ft. above platform height; metric working height is 2 meters above platform height.

Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate UpRight Operator's manual for detailed instructions on the proper use and maintenance of this equipment. UpRight also manufactures a complete line of aluminum scaffolding and other aerial work platforms. Contact your UpRight distributor for information on other products.

UpRight

USA (800) 926-5438, (209) 891-5200 FAX (209) 896-9012

1775 Park Street, Selma CA 93662

Europe (353) 1-202-4100 FAX (353) 1-202-4101

Pottery Road, Dun Laoire, Ireland

www.upright.com e-mail: marketing@upright.com

Printed in U.S.A. Copyright UpRight, Inc. 1998.

Form No. 6095-980210-A