Trailer Mount


Upright POWERED ACCESS



TL37 trailer mount specifications

| | TL37 TRAILER MOUNT |
|----------------------------------|--|
| max. working height | 13.2m |
| max. platform height | 11.2m |
| max. outreach | 5.9m |
| platform capacity (SWL) | 215kg |
| outrigger footprint | 3.60m(A) x 3.00m(B) |
| turret rotation (non-continuous) | 640° |
| platform rotation | 90° |
| platform depth C | 0.80m |
| platform width D | 1.20m |
| stowed height E | 1.95m |
| towing length F | 6.30m |
| towing width G | 1.48m |
| weight (battery model) | 1,390kg* |
| control system | fully proportional hydraulic controls at basket and ground |
| power source | 24V battery (4 x 6V 195ah batteries) or 230V mains |
| power options | bi-energy (petrol & battery) power |

^{*} Machine towing weight depends on power configuration and supply of optional extras Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only







Vigo Centre, Birtley Road, Washington, POWERED ACCESS Tyne & Wear, NE38 9DA, U.K.

TL37 6/09

Sales Tel: +44 (0) 845 1550 057 • Spare Parts Tel: +44 (0) 845 1550 058

www.upright.com

standard features

- 1.3m jib with 130° working arc
- In-line boom design for maximum rigidity
- 6.3m travel length
- 1390kg towing weight
- 90° hydraulically powered platform rotation
- Cycle protection guards
- Hand pump emergency lowering from platform
- Lock valves on all hydraulic cylinders
- Proportional live hydraulic controls
- Automatic reversing and overrun braking
- Integral road lighting board
- 24V battery (4 x 6V 195ah batteries) or 230V mains power
- 1 year parts and labour warranty
- 5 year structural warranty

options

- On-board 230V generator for mains powered units
- Bi-Energy (petrol and DC battery) power
- GRP platform
- Special paint colours

Other options available on request

