Compact Scissor Lifts

Upright POWERED ACCESS



- ☐ 12.1m working height
- □ Bi-energy power source
- Lightweight with excellent ground clearance
- ☐ 4 wheel drive
- □ Large platform area with 1.2m deck extension
- 4 hydraulic outriggers with auto-level
- Non-marking tyres

X27BE X33BE

X27/33BE bi-energy scissor lifts specifications

	X27BE	X33BE
max. working height	10.3m	12.1m
max. platform height	8.2m	10.1m
max. drive height	8.2m	10.1m
platform capacity (SWL)	580kg	450kg
platform size (deck extended) 3.94m x 1.65m	3.94m x 1.65m
deck extension	1.2m	1.2m
overall width B	1.77m	1.77m
overall length C	3.36m	3.36m
lowered height A	2.56m	2.7m
min height (guardrails folded)	1.75m	2.0m
gross weight	3110kg	3840kg
inside turning radius	2.83m	2.83m
outside turning radius	4.60m	4.60m
max. drive speed (lowered)	4.5km/h	4.5km/h
ground clearance	350mm	350mm
gradeability (diesel engine)	35%	35%
gradeability (batteries)	25%	25%
tyres	non-marking 27-1	0.5-15 poly filled
drive system	4 wheel drive	
power source	Kubota D-905 water cooled diesel 22.5hp and 4 x 6v 305Ah deep-cycle batteries	

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate UpRiaht Operators manual for detailed instructions on the proper use and maintenance



Upright Vigo Centre, Birtley Road, Washington, POWERED ACCESS Tyne & Wear, NE38 9DA, U.K.

X33BE

Sales Tel: +44 (0) 845 1550 057 • **Spare Parts Tel:** +44 (0) 845 1550 058

standard features

- Bi-energy power source
- 1.2m roll-out deck extension
- 4 wheel drive
- 4 hydraulic outriggers with auto-level
- Proportional joystick control
- Non-marking tyres
- Articulating axle
- Driveable at full height
- Operator horn
- Drive motion alarm
- Lower warning alarm
- Fold-down guardrails
- 1 year parts and labour warranty
- 5 year structural warranty

options

- 110/240v power line to platform
- Special paint colours
- Environmental green oil







